



Specificaties

Product	760 125	760 150	HE 760 125 (Tolerantie)
Spectrum	R90G5B5	R90G5B5	R90G5B5
Dimmable SKU	HGC906516	HGC906517	HGC906539
PPF Output (400-700 nm)	2650 $\mu\text{mol/s}$	2570 $\mu\text{mol/s}$	2900 $\mu\text{mol/s}$
PF Output (400-800 nm)	2650 $\mu\text{mol/s}$	2570 $\mu\text{mol/s}$	2900 $\mu\text{mol/s}$
PPE (at 100% power)	3.5 $\mu\text{mol/J}$	3.38 $\mu\text{mol/J}$	3.85 $\mu\text{mol/J}$
PE (at 100% power)	3.5 $\mu\text{mol/J}$	3.38 $\mu\text{mol/J}$	3.85 $\mu\text{mol/J}$
Optics	125°	150°	125°

Algemeen

Alle types	Waarde	(Tolerantie)
Input Voltage	347/400 V	$\pm 10\%$
Input Current	2.2/1.9 A	$\pm 10\%$
Input Power	760 W	$\pm 3\%$
Mains Frequency	50/60 Hz	-
Power Factor	> 0.95	-
Isolation Class	Class I	-
IP Rating	IP66	-
THD	< 15%	-
Inrush Current	< 25 A	-
Leakage Current	< 2.5 mA	-
Connector	Wieland RST 2013 GN	-
Afmetingen (L x B x H)	62 x 30 x 11.8 cm	$\pm 1\%$
Weight	12.1 kg	$\pm 3\%$
Temperature Ambient	0 - 45 °C	-
Light Maintenance (L90)	36000 h	-